

MODEL FL – FULL ACCESS CURTAIN STYLE DOCK SEAL



FEATURE SUMMARY

- Improves Safety & Productivity While Reducing Costs by Providing Protection From Inclement Weather, Dirt & Insects While Saving Energy
- High-Tear Abrasion Resistant Fabrics With Polyester Base & Double Lock Stitched Seams Suitable to Temperatures of – 40 Degrees
- Kiln Dried Superior Grade Backing Lumber
- 99 % Memory Foam Core For Extended Life
- Velcro Split Drop Curtain With Ropes & Pulleys Adjustable to Suit Varying Truck Heights
- Bottom Corner Draft Pads For Additional Sealing
- Condensation Drainage System
- 24” High Yellow Guide Stripes on Bottom of Pads for Accurate Truck Positioning
- Most Suitable for Door Openings Up To 10 Feet Wide x 10 Feet High
- Galvanized Mounting Hardware Included

DESCRIPTION

The WEARTOUGH® Series of dock seals provide effective protection for personnel and cargo while loading and off loading trailers. The truck pushes tight against the sides and top of the seal to help keep out inclement weather, dust and insects creating a more productive and safer environment while saving energy costs and increasing security.

SPECIFICATON

Dock door seal(s) to be Model FL as manufactured by Nordock Inc. to suit door size of _____ wide x _____ high and dock height of _____ with a projection of _____ to provide 10”-12” beyond front face of dock bumpers. Each unit shall consist of (2) two side pads and one head curtain. Taper side pads if needed to suit an approach grade percentage of _____. Side pads to be constructed with 99% compression recovery polyurethane foam core continuously bonded to kiln dried superior backing lumber and fully wrapped with coated polyester base fabric. The fabric shall be coated with _____. The second layer of fabric for wear pleats shall be _____ with a _____” face exposure. Head curtain drop shall be 30” long or _____ to provide 6” overlap with the lowest trailer/truck to be serviced. The curtain shall be equal to the overall unit width and be adjustable with velcro splits. The unit shall include 24” high _____ or optional full height _____ yellow guide stripes to aid in trailer positioning.

WARRANTY

Nordock guarantees that the FL Model of dock seals will perform as described and to the full satisfaction of the purchaser for one-year from date of receipt. Consult your Nordock representative for assistance in choosing the correct size and options for your application.

FABRIC OPTIONS:

22 oz. & 40 oz. Vinyl
16 oz. & 40 oz. Hypalon
50oz. WT 90 WEARTOUGH™

SEAL OPTIONS:

4”, 6” & 8” Exposure Wear Pleats
Half or Full Foam Filled Curtain
Full Height Yellow Guide Stripes
Additional Head Curtain Drop

ADDITIONAL EQUIPMENT OPTIONS:

Galvanized Steel Canopies
Loading Dock Lights



* Nordock Inc. reserves the right to make changes to specifications without notice or obligation.

NORDOCK® INC.

Nordock products are covered by various domestic and foreign patents & applications.

Website: www.nordockinc.com ~ Email: Sales@nordockinc.com ~ Toll Free: 866-885-4276