

HYDRAULIC DOUBLE SCISSOR LIFT

STANDARD CAPACITY UP TO 20,000 POUNDS
STANDARD TRAVEL UP TO 16 FEET




FEATURE SUMMARY

- Self Aligning Spherical Bearings and Lifetime Lubricated Bushings at all Pivot Points
- Cam Follower Rollers with High Tensile Needle Bearing Construction
- High Performance Cylinders with Chrome Rod, Guide Bearing, Scraper and Safety Velocity Fuse
- Guardrails with Kick Plate on Non-Access Sides and Chains with Snap Release on Access Sides
- Two Control Stations Provided
- Over-Travel Limit Switch
- Remote Mounted Power Unit Supplied With Oil and High Pressure Hose
- Motor Controller with Dust Tight Enclosure and Reduced Voltage to Water Tight Push Button Stations
- Checker Plate Deck Surface



**SPHERICAL
CENTER
BEARING**



**CAM
FOLLOWER**



**POWER
UNIT**

OPTIONAL EQUIPMENT

- Deck Perimeter Electric Stops
- Custom Guarding, Gates & Interlocks
- Full Travel Stabilizer Guides
- Levelling & Anti-Creep Switches
- Roll Off Stops
- Numerous Custom Performance and Safety Options Available